

2017 COMMANDER™ DPS 800R

L7e HOMOLOGATION

HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok[‡] QE auto-locking front differential
- Industry's exclusive Dual-Level™ cargo box
- 14-in. cast-aluminum wheels with 27-in. Maxxis Bighorn 2.0[†] tires
- Adjustable driver's seat and tilt steering



Model presented:
Commander 800R Light Grey, INT version

AVAILABLE MODELS

■ Light Grey / 800R (L7e)

ENGINES	800R
Type	Rotax 799.9 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT, L / H / N / R / P, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
CO Emissions	Euro-2 approved

SUSPENSIONS	
Front Suspension	Double A-arm with dive-control geometry 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) with external sway bar 10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks sur version us

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES (EC approved) / WHEELS	
Front Tires	Maxxis Bighorn 2.0 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)
Wheels	14 in. cast aluminum

DIMENSIONS / CAPACITIES	
L x W x H	118.3 x 58.6 x 72 in. (300.4 x 148.9 x 182.9 cm)
Wheelbase	75.8 in. (192.4 cm)
Ground Clearance	11 in. (27.9 cm)
Dry Weight*	1,287 lb (584 kg)
Rack Capacity	600 lb (272 kg) Dual-Level cargo box Upper level: 400 lb (181 kg) Lower level: 200 lb (91 kg)
Storage Capacity	Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)
Towing Capacity	270 kg (595 lb.)
Fuel Capacity	10 gal (37.8 L)

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for winch	Lighting	240-W from four 60-W projectors with tail lights / brake lights
Protection	N/A	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
EC specificities	Turning lights & brake lights, mirrors, horn, EC seat belts, lockable gas trap & 2nd recreation D.E.S.S key		

WARRANTY

EC models : 2 years warranty.

All L7e models are limited to 15 Kw/20 hp and equipped with L7e homologation required equipments. L7e models engines are compliant with L7e standards in force. Towing capacities of L7e models respect applicable L7e homologation requirements.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am



Can-AmOffroad.com