

2017 MAVERICK™ MAX X DS 1000R TURBO

INTERNATIONAL

HIGHLIGHTS

- 131-hp Rotax® 1000R Turbocharged V-twin engine
- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok† QE auto-locking front differential
- Front and rear FOX† 2.5 PODIUM QS3† shocks
- Adjustable driver's seat and tilt steering
- Passenger handhold and grab bar



Model presented:
Maverick MAX X ds 1000R TURBO White, Hyper Silver & Octane Blue, INT version

AVAILABLE MODELS

 Hyper Silver & Octane Blue / 1000R (INT)

ENGINES	1000R TURBO
Type	Rotax 976 cc Turbocharged V-twin engine with forged pistons, liquid cooled with integrated intercooler & Donaldson high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow, L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 15 in. (38.1 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound and dual rate spring preload adjustments
Rear Suspension	Torsional Trailing A-arms independent rear suspension (TTA) with sway bar 16 in. (40.6 cm) travel
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound, dual rate spring preload adjustments and spring crossover, bottom-out control

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers

FEATURES	
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off
Winch	Prewired for winch
Protection	Front bumper
Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Lighting	240-W from four 60-W projectors with tail lights / brake lights
Anti-theft System	Digitally Encoded Security System (D.E.S.S)

WARRANTY
INT models : 2 years warranty.

TIRES / WHEELS	
Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14 in. aluminum beadlock

DIMENSIONS / CAPACITIES	
L x W x H	146.5 x 64 x 78 in. (372.1 x 162.5 x 198 cm)
Wheelbase	117.5 in. (298.5 cm)
Ground Clearance	13 in. (33 cm)
Dry Weight*	1,649 lb (748 kg)
Rack Capacity	150 lb (68 kg) with LinQ quick-attach
Storage Capacity	Glove box: 4.5 gal (17.2 L) Center console: 0.3 gal (1.3 L)
Towing Capacity	N/A
Fuel Capacity	10 gal (37.8 L)

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am

Can-AmOffroad.com

