

# 2017 OUTLANDER™ 570 DPS

L7e HOMOLOGATION

## HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- Visco-Lok<sup>®</sup> QE auto-locking front differential
- 12-in. cast-aluminum wheels
- Multifunction digital gauge

## AVAILABLE MODELS

Green / 570 (L7e)



Model presented:  
Outlander 570 DPS Green, INT version

ENGINES	570
Type	Rotax 570 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
CO Emissions	Euro-2 approved

## SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 8.8 in. (22 cm) travel
Rear Shocks	Oil

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

## FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	70-W from dual 35-W front light / brake light
Protection	N/A	Seat	N/A
EC specifications	Turning lights & brake lights, mirrors, horn, lockable gas cap & storage, 2nd recreation D.E.S.S key (not RF), 2x4 compliant braking system, transmission lockable in park mode		
EC specifications	Anti-theft System		
	N/A		

## WARRANTY

EC/L7e models : 2 years warranty.

All L7e models are limited to 15 Kw/20 hp and equipped with L7e homologation required equipments. L7e models engines are compliant with L7e standards in force. Towing capacities of L7e models respect applicable L7e homologation requirements.

## TIRES (EC approved) / WHEELS

Front Tires	Carlisle <sup>†</sup> Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

## DIMENSIONS / CAPACITIES

L x W x H	83 x 46 x 49 in. (211 x 116.8 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	33.8 in. (85.8 cm)
Dry Weight*	704 lb (319 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	135 kg (300 lb.)
Fuel Capacity	5.4 gal (20.5 L)

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

**can-am**



Can-AmOffroad.com