

2017 OUTLANDER™ MAX XT 570

T3 HOMOLOGATION

HIGHLIGHTS

- 3,000-lb (1,361 kg) WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- Wind deflectors
- Dynamic passenger comfort ergonomics
- Multiposition passenger

AVAILABLE MODELS

■ Pure Magnesium / 570 (T3,INT)



Model presented:
Outlander MAX XT 570 Pure Magnesium, INT version

ENGINES

	570
Type	48 hp, Rotax 570 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE [‡] auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22 cm) travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Lighting	70 W from dual 35-W front light / brake light
Protection	Heavy-duty front & rear bumpers Handlebar wind deflectors	Seat	Convertible Rack System (CRS)
T3 specificities	Turning lights & brake lights, mirrors, horn, lockable gas cap & storage, 2x4 compliant braking system, transmission lockable in park mode, towing hitch, seat with backrest & trailer plug		
Anti-theft System	Digitally Encoded Security System (D.E.S.S)		

WARRANTY

T3 models : 2 years warranty.

TIRES / WHEELS

Front Tires	Maxxis M923J 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	Maxxis M923J 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	91 x 46 x 52.5 in. (231 x 116.8 x 133 cm)
Wheelbase	59 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	33.8 in. (85.8 cm)
Dry Weight*	741 lb (336 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	750kg trailer with brakes 590kg trailer without brakes
Fuel Capacity	5.4 gal (20.5 L)

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am

Can-AmOffroad.com



2017 OUTLANDER™ MAX XT 570

INTERNATIONAL

HIGHLIGHTS

- 3,000-lb (1,361 kg) WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- Wind deflectors
- Dynamic passenger comfort ergonomics
- Multiposition passenger

AVAILABLE MODELS

■ Pure Magnesium / 570 (T3,INT)



Model presented:
Outlander MAX XT 570 Pure Magnesium, INT version

ENGINES	570
Type	48 hp, Rotax 570 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE ⁺ auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22 cm) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	Maxxis M923J 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	Maxxis M923J 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES	
L x W x H	91 x 46 x 52.5 in. (231 x 116.8 x 133 cm)
Wheelbase	59 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	33.8 in. (85.8 cm)
Dry Weight*	741 lb (336 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Lighting	70 W from dual 35-W front light / brake light
Protection	Heavy-duty front & rear bumpers Handlebar wind deflectors	Seat	Convertible Rack System (CRS)
		Anti-theft System	N/A

WARRANTY

INT models : 2 years warranty.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am



Can-AmOffroad.com