

2017 RENEGADE® 570

L7e HOMOLOGATION

HIGHLIGHTS

- Continuously Variable Transmission (CVT) with engine braking
- 12-in. cast-aluminum wheels with 25-in. ITP Holeshott† ATR tires
- Visco-Lok† auto-locking front differential
- Multifunction digital gauge



AVAILABLE MODELS

■ Can Am Red / 570 (L7e)

Model presented:
Renegade 570 Can Am Red, INT version

ENGINES	570
Type	Rotax 570 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential
Power Steering	N/A
CO Emissions	Euro-2 approved

TIRES (EC approved) / WHEELS	
Front Tires	ITP Holeshott ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshott ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	Oil

DIMENSIONS / CAPACITIES	
L x W x H	86 x 46 x 49 in. (218.4 x 116.8 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	615 lb (279 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	135 kg (300 lb.)
Fuel Capacity	5.4 gal (20.5 L)

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brakes with hydraulic twin-piston caliper

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240-W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
Protection	Front bumper, optional wind deflectors	Seat	N/A
EC specificities	Turning lights & brake lights, mirrors, horn, lockable gas cap & storage, 2nd recreation D.E.S.S key (not RF), 2x4 compliant braking system, transmission lockable in park mode	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)

WARRANTY

EC models : 2 years warranty.

All L7e models are limited to 15 Kw/20 hp and equipped with L7e homologation required equipments. L7e models engines are compliant with L7e standards in force. Towing capacities of L7e models respect applicable L7e homologation requirements.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved. ™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am



Can-AmOffroad.com