

# 2017 OUTLANDER™ X® mr 1000R

INTERNATIONAL

## HIGHLIGHTS

- Front and rear FOX† 1.5 PODIUM† QS3 shocks
- 30-in. Gorilla Axle Silverback† tires on 14-in. cast-aluminum wheels
- Relocated radiator
- 3,000-lb (1,361 kg) WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Mudguards & Mud-riding footrests

## AVAILABLE MODELS

White, Black & Can-Am Red / 1000R



Model presented:  
Outlander X mr 1000R White, Black & Can-Am Red,  
INT version

## ENGINES

### 1000R

Type	Rotax 976 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

## SUSPENSIONS

Front Suspension	Double A-arm
Front Shocks	FOX Performance Series 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI)
Rear Shocks	FOX Performance Series 1.5 PODIUM RC2

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

## TIRES / WHEELS

Front Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14 in. ITP SS312 cast aluminum

## DIMENSIONS / CAPACITIES

L x W x H	97 x 50 x 51.5 in. (246 x 127 x 131 cm)
Wheelbase	59 in. (149.9 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	36.75 in. (93.3 cm)
Dry Weight*	990 lb (449 kg)
Rack Capacity	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

## FEATURES

Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	Heavy-duty front & rear bumpers, aluminum taper-profile handlebar with wind deflectors and square pad, mud-riding footrests and mudguards	Seat	N/A
		Anti-theft System	RF Digitally Encoded Security System (RF D.E.S.S.)

## WARRANTY

INT models : 2 years warranty.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

**can-am**



Can-AmOffroad.com