

2017 OUTLANDER™ PRO 650/1000

T3 HOMOLOGATION

HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- 12-in. cast-aluminum wheels with 26-in. Carlisle ACT HD radial tires
- Relocated air intakes
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- Digitally Encoded Security System (D.E.S.S.™)



Model presented:
Outlander Pro 650 Light Grey, T3 version

AVAILABLE MODELS

■ Light Grey / 650 (T3, INT) / 1000 (T3)

ENGINES	650	1000
Type	Rotax 649.6 cc V-twin, liquid cooled	Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

TIRES / WHEELS

Front Tires	Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12 in. Cast Aluminum

SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel	Double A-arm with increased suspension pre-load 229 mm travel
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) with increased suspension pre-load 236 mm travel	
Rear Shocks	Oil	

DIMENSIONS / CAPACITIES

L x W x H	86 x 46 x 49.5 in. (218.4 x 116.8 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	726 lb (329 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	750kg trailer with brakes 590kg trailer without brakes
Fuel Capacity	5.4 gal (20.5 L)

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES

Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	1,361 kg WARN winch with roller fairlead	Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	N/A	Seat	N/A
T3 specificities	Turning lights & brake lights, mirrors, horn, lockable gas cap & storage, 2x4 compliant braking system, transmission lockable in park mode, towing hitch, seat with backrest & trailer plug		
Additional features	2-in (5cm) tow ball		
Anti-theft System	Digitally Encoded Security System (D.E.S.S.)		

WARRANTY

T3 models : 2 years warranty.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am



Can-AmOffroad.com

2017 OUTLANDER™ PRO 650

INTERNATIONAL

HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- 12-in. cast-aluminum wheels with 26-in. Carlisle ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- Digitally Encoded Security System (D.E.S.S.™)

AVAILABLE MODELS

■ Light Grey / 650 (T3, INT)



Model presented:
Outlander Pro 650 Light Grey, INT version

ENGINES	650
Type	Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12 in. Cast Aluminum

DIMENSIONS / CAPACITIES	
L x W x H	86 x 46 x 49.5 in. (218.4 x 116.8 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	726 lb (329 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	Prewired for available winch	Seat	Reinforced seat skin
Protection	N/A	Anti-theft System	RF Digitally Encoded Security System (RF D.E.S.S.)

WARRANTY

INT models : 2 years warranty.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am



Can-AmOffroad.com