

2017

RENEGADE® ENDURO™

PACKAGE HIGHLIGHTS

- Heated seat
- RAS™ 2 front suspension
- REV-XS™ platform
- rMotion™ with Air Ride rear suspension
- 15 × 137 × 1.25 in. Ice Ripper XT track
- HPG™ Plus aluminum front shocks
- Adjustable Pilot™ TS Skis
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse
- Multifunction digital gauge with display
- 12V power outlet and heated visor outlets for driver
- RF D.E.S.S.™ key
- REV-XP™ X seat with 5 L / 1.3 us gal of storage

EXTRA HIGHLIGHTS

- 900 ACE & 1200 4-TEC
- Reversible throttle lever (thumb or finger activated)
 - iTC™ Engine mapping modes (Standard, Sport or ECO)
 - Learning-Key included
 - Engine oil cooler
 - Mechanical reverse
- 1200 4-TEC only
- Extended heat exchanger for better cooling capacity



600 H.O. E-TEC shown

ROTAX® ENGINE

	600 H.O. E-TEC®	800 R-E-TEC®	900 ACE	1200 4-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	2	3	3
Displacement	594.4 cc / 36.3 in. ³	799.5 cc / 48.8 in. ³	899.0 cc / 54.9 in. ³	1170.7 cc / 71.4 in. ³
Bore	72 mm / 2.8 in.	82 mm / 3.2 in.	74 mm / 2.9 in.	91 mm / 3.6 in.
Stroke	73 mm / 2.9 in.	75.7 mm / 3 in.	69.7 mm / 2.7 in.	60 mm / 2.4 in.
Maximum engine speed	8100 RPM	7900 RPM	7250 RPM	7800 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection	EFI	EFI
Recommended fuel type	Premium unleaded	Premium unleaded	Regular unleaded	Regular unleaded
Minimum octane	91	91	87	87
Fuel tank	40 liters / 10.6 gallons	40 liters / 10.6 gallons	40 liters / 10.6 gallons	40 liters / 10.6 gallons
Oil tank capacity	3.7 liters / 3.9 quarts	3.7 liters / 3.9 quarts	3.3 liters / 3.5 quarts	3.5 liters / 3.7 quarts

POWERTRAIN

	TRA™ III	TRA™ VII	eDrive™ 2	eDrive™ 2
Drive clutch type	TRA™ III	TRA™ VII	eDrive™ 2	eDrive™ 2
Driven clutch type	QRS	QRS	QRS (short shaft)	QRS
Engagement	3400 RPM	3800 RPM	2200 RPM	2200 RPM
Small sprocket number of teeth	25	25	24	24
Large sprocket number of teeth	45	45	49	45
Drive sprocket number of teeth	8	8	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line	Brembo brake with braided stainless-steel brake line

DRY WEIGHT

223 kg / 492 lb	227 kg / 501 lb	235 kg / 518 lb	246 kg / 543 lb
-----------------	-----------------	-----------------	-----------------

FEATURES

Frame	REV-XS™	Reverse	RER™ (600 H.O., 800R) Electronic (900 ACE, 1200 4-TEC)	Mirrors	Optional
Skis	Pilot™ TS	Heated throttle lever	Standard	Windshield	375 mm / 15 in.
Seating	REV-XP™ X heated with storage	Heated grips	Standard	Runner	Adjustable blade 1/4
Handlebar	Aluminum with J-hooks	Gauge	Multifunction	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	115 mm / 4.5 in.			Hitch	Optional
Electric start	Standard				

COLOUR

Northern Lichen 

Black 

DIMENSIONS

Vehicle overall length	3110 mm / 122.4 in.
Vehicle overall width	1217 mm / 47.9 in.
Vehicle overall height	1210 mm / 47.6 in.
Ski stance	1077 mm / 42.4 in.
Ski overall length	1066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3487 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. Ice Ripper XT

SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus
Front suspension max. travel	229 mm / 9 in.
Rear suspension	rMotion™
Center shock	HPG™
Rear shock	Air RIDE
Rear suspension max. travel	270 mm / 10.6 in.



1200 4-TEC shown



800R E-TEC shown

FEATURE HIGHLIGHTS



RAS™ 2 Front suspension

A taller ski spindle, refined geometry and lighter components sharpen the sled's already precise handling, especially in extreme conditions.



Air RIDE rear suspension

Tailors the ride for load or trail conditions via a rear air spring and an onboard compressor. Five preload settings are selectable on-the-fly via a handlebar rocker switch.



Adjustable Pilot™ TS Skis

Radical concept enables the rider to literally dial in the amount of ski bite for conditions and riding style in seconds. A knob adjacent to the ski leg raises or lowers the ski runner – fully extended for very aggressive bite. There are 20 settings over a .5 in. / 12.5 mm range.



LinQ™ cargo system (option)

Our cargo attachment system is the hassle-free way to connect cargo bags or a fuel caddy to your sled in seconds.



Multifunction gauge with LCD screen

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard