

2017 MXZ[®] X-RS[®] IRON DOG

PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- REV-XS™ RS chassis with adjustable forward steering post
- rMotion™ rear suspension
- 15 x 129 x 1.25 2-ply RipSaw⁺ track
- KYB⁺ Pro 40 aluminum piggyback front and rear shocks with Easy-Adjust compression adjuster (22 clics)
- Brembo racing brake with braided stainless-steel brake line
- 8-tooth racing sprocket with reinforced drive shaft
- Transparent handguards
- REV-XP[®] X[®] narrow seat with 5 L / 1.3 gal of storage
- Backlit multifunction steering controls
- Multifunction digital gauge with display and 5 minutes high sampling rate record mode
- Pilot 5.7™ skis with 7/16 in. (1.1 cm) round runner and 90° carbide



MXZ[®] X-RS[®] Iron Dog 600 H.O. E-TEC shown

ROTAX[®] ENGINE

600 H.O. E-TEC[®]

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4cc / 36.3 in. ³
Bore	72 mm / 2.8 in.
Stroke	73 mm / 2.9 in.
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	91
Fuel tank	40 liters
Oil tank capacity	3.7 liters

POWERTRAIN

Drive clutch type	TRA™ III
Driven clutch type	QRS
Engagement	3400 RPM
Small sprocket number of teeth	25
Large sprocket number of teeth	45
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm / 7.2 in.
Brake system	Brembo racing brake with stainless-steel braided brake line

DRY WEIGHT

213 kg / 469 lb

COLOUR

Carbon Black 

DIMENSIONS

Vehicle overall length	3010 mm / 118.5 in.
Vehicle overall width	1217 mm / 47.9 in.
Vehicle overall height	1210 mm / 47.6 in.
Ski stance	1077 mm / 42.4 in.
Ski overall length	1066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3269 mm / 129 in.
Track profile height	31.8 mm / 1.25 in. RipSaw 2 ply

SUSPENSION

Front suspension	RAS™ 2
Front shock	KYB Pro 40 R Easy-Adjust
Front suspension max. travel	241 mm / 9.5 in.
Rear suspension	rMotion with reinforcements
Center shock	KYB Pro 40 Easy-Adjust
Rear shock	KYB Pro 40 Easy-Adjust
Rear suspension max. travel	272 mm / 10.7 in.

FEATURES

Frame	REV-XS™ RS	Reverse	RER™	Mirrors	Optional
Skis	Pilot™ 5.7	Heated throttle lever	Standard	Windshield	152 mm / 6 in.
Seating	REV-XP X narrow with storage	Heated grips	Standard	Runner	Round 7/16
Handlebar	Straight aluminum with J-hooks	Gauge	Multifunction	Carbide configuration	102 mm at 90°
Riser block height	130 mm / 5.1 in.	Electric start	Standard	Hitch	Optional