

2017

ADVENTURE LX



ROTAX® ENGINE

600 ACE

| | |
|-----------------------|--|
| Engine details | Liquid-cooled, four-stroke D.O.H.C., dry sump |
| Cylinders | 2 |
| Displacement | 600 cc |
| Bore | 74 mm |
| Stroke | 69.7 mm |
| Maximum engine speed | 7250 RPM |
| Carburation | EFI |
| Recommended fuel type | Regular unleaded |
| Minimum octane | 95 |
| Fuel tank | 38 liters |
| Oil tank capacity | 2.1 liters |

POWERTRAIN

| | |
|--------------------------------|---|
| Drive clutch type | eDrive |
| Driven clutch type | QRS SS |
| Small sprocket number of teeth | 21 |
| Large sprocket number of teeth | 51 |
| Drive sprocket number of teeth | 8 |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

FEATURES

| | |
|-----------|--|
| Frame | REX ² |
| Skis | Blade |
| Seating | 2-up |
| Handlebar | Straight steel with hooks, 130 mm riser |
| Reverse | Mechanical |

COLOUR

Red/Black 

DIMENSIONS

| | |
|------------------------|-------------|
| Vehicle overall length | 3100 mm |
| Vehicle overall width | 1245 mm |
| Vehicle overall height | 1455 mm |
| Ski stance | 1080 mm |
| Track nominal width | 381 mm |
| Track nominal length | 3487 mm |
| Track profile height | 34 mm Cobra |

SUSPENSION

| | |
|------------------|------------------------|
| Front suspension | A-LFS+ |
| Front shock | HPG 25 |
| Rear suspension | PPS ² -3500 |
| Center shock | HPG 25 |
| Rear shock | HPG 36 |

| | |
|----------------|---------------------|
| Heated grips | STD |
| Gauge | Analog with display |
| Electric start | STD |
| Mirrors | Accessory |
| Windshield | 635 mm |
| Hitch | Accessory |