

2017

# BOONDOCKER 3700



## ROTAX® ENGINE

	600 E-TEC	800R E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™	
Cylinders	2	
Displacement	594.4 cc	799.5 cc
Bore	72 mm	82 mm
Stroke	73 mm	75.7 mm
Maximum engine speed	8100 RPM	7900 RPM
Carburation	Electronic Direct Injection	
Recommended fuel type	Premium unleaded	
Minimum octane	95	
Fuel tank	38 liters	
Oil tank capacity	3.7 liters	

## POWERTRAIN

	TRA 3	TRA 7
Drive clutch type	TRA 3	TRA 7
Driven clutch type	QRS +3mm	
Small sprocket number of teeth	19	21
Large sprocket number of teeth	49	49
Drive sprocket number of teeth	8	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

## FEATURES

Frame	REX <sup>2</sup>
Skis	Blade DS
Seating	BD, 1-up
Handlebar	U-type steel, 115 mm riser, mountain strap
Reverse	RER

## COLOUR

Black/Sunburst Yellow 

## DIMENSIONS

Vehicle overall length	3200 mm
Vehicle overall width	1105 mm
Vehicle overall height	1250 mm
Ski stance	921 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3705 mm
Track profile height	64 mm PowderMax FlexEdge

## SUSPENSION

Front suspension	A-LFS+
Front shock	HPG 36
Rear suspension	PPS <sup>2</sup> -3700-DS
Center shock	HPG 36
Rear shock	HPG 36