

2017

69 YETI ARMY



ROTAX® ENGINE

600 E-TEC

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Premium unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity	3.7 liters

POWERTRAIN

Drive clutch type	TRA 3
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.23:1 ratio
Large sprocket number of teeth	2nd gear = 1.98:1 ratio
Drive sprocket number of teeth	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	L-XU
Skis	Blade
Seating	2-up
Handlebar	U-type steel with hooks, adjustable riser, mountain strap
Reverse	Mechanical (2F-N-R)

COLOUR

Squadron Green/Black 

DIMENSIONS

Vehicle overall length	3270 mm
Vehicle overall width	1120 mm
Vehicle overall height	1430 mm
Ski stance	900 mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm Ice Ripper (studded)

SUSPENSION

Front suspension	LTS
Front shock	MC
Rear suspension	PPS-6900-A
Center shock	HPG 25
Rear shock	HPG 36

Heated grips	STD
Gauge	Analog with display
Electric start	STD
Mirrors	STD
Windshield	High (510 mm), one piece
Hitch	STD