

2017 RENEGADE[®] X[®]

PACKAGE HIGHLIGHTS

- RAS™ 2 front suspension
- REV-XS™ platform
- rMotion™ rear suspension
- RipSaw[†] or Ice Ripper XT 1.25 in. lug track choice
- KYB[†] Pro 36 aluminum piggyback rear shock with Easy-Adjust compression adjusters (22 clics)
- HPG™ Plus R aluminum front shocks with no-tool rebound adjuster (22 clics)
- RER™ electronic reverse
- Engine temperature gauge
- Backlit multifunction steering controls
- RF D.E.S.S.™ key
- REV-XP™ X seat with 1.3 us gal of storage
- Transparent handguards
- Optional Adjustment package including rMotion™ Quick Adjust™ system and Pilot™ TS skis

EXTRA HIGHLIGHTS

- 1200 4-TEC
- iTC™ Engine mapping modes (Standard, Sport or ECO)
- Reversible throttle lever (thumb or finger activated)
- Learning-Key included
- Mechanical reverse
- Extended heat exchanger for better cooling capacity
- Engine oil cooler



600 H.O. E-TEC shown

ROTAX® ENGINE

	600 H.O. E-TEC®	1200 4-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	594.4 cc / 36.3 in. ³	1170.7 cc / 71.4 in. ³
Bore	72 mm / 2.8 in.	91 mm / 3.6 in.
Stroke	73 mm / 2.9 in.	60 mm / 2.4 in.
Maximum engine speed	8100 RPM	7800 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	91	87
Fuel tank	40 liters / 10.6 gallons	40 liters / 10.6 gallons
Oil tank capacity	3.7 liters / 3.9 quarts	3.5 liters / 3.7 quarts

POWERTRAIN

Drive clutch type	TRA™ III	eDrive™ 2
Driven clutch type	QRS	QRS
Engagement	3400 RPM	2200 RPM
Small sprocket number of teeth	23	24
Large sprocket number of teeth	45	45
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo racing brake with stainless-steel braided brake line	Brembo racing brake with stainless-steel braided brake line

DRY WEIGHT

216 kg / 476 lb	235 kg / 518 lb
-----------------	-----------------

COLOUR

Orange Crush 
Black 

DIMENSIONS

Vehicle overall length	3110 mm / 122.4 in.
Vehicle overall width	1217 mm / 47.9 in.
Vehicle overall height	1210 mm / 47.6 in.
Ski stance	1077 mm / 42.4 in.
Ski overall length	1066 mm / 42 in.
Track nominal width	381 mm / 15 in.
Track nominal length	3487 mm / 137 in.
Track profile height	31.8 mm / 1.25 in. RipSaw or 31.8 mm / 1.25 in. Ice Ripper XT [†]

SUSPENSION

Front suspension	RAS™ 2
Front shock	HPG™ Plus R
Front suspension max. travel	229 mm / 9 in.
Rear suspension	rMotion™
Center shock	HPG™ Plus
Rear shock	KYB [†] Pro 36 EA
Rear suspension max. travel	270 mm / 10.6 in.
rMotion Quick Adjust System	Optional

FEATURES

Frame	REV-XS™	Reverse	RER™ (600 H.O.) Mechanical (1200 4-TEC)	Mirrors	Optional
Skis	Pilot™ 5.7 Pilot™ TS (Optional)	Heated throttle lever	Standard	Windshield	285 mm / 12 in.
Seating	REV-XP™ X with storage	Heated grips	Standard	Runner	Square 5/16
Handlebar	Aluminum with J-hooks	Gauge	Multifunction	Carbide configuration	102 mm / 4 in. at 90°
Riser block height	130 mm / 5.1 in.	Electric start	Standard	Hitch	Optional



1200 4-TEC shown



1200 4-TEC shown

FEATURE HIGHLIGHTS



RAS™ 2 Front suspension

A taller ski spindle, refined geometry and lighter components sharpen the sled's already precise handling, especially in extreme conditions.



Transparent handguards

Their design increases protection and makes sleds look even lighter. They're ready for industry-first LED accent lighting, flip-out mirrors and semi-rigid extensions. (Available as accessories).



Adjustable Pilot™ TS Skis (option)

Radical new concept enables the rider to literally dial in the amount of ski bite for conditions and riding style in seconds. A knob adjacent to the ski leg raises or lowers the ski runner – fully extended for a very aggressive bite. There are 20 settings over a .5 in. / 12.5 mm range.



LinQ™ cargo system (option)

Our cargo attachment system is the hassle-free way to connect cargo bags or a fuel caddy to your sled in seconds.



Multifunction gauge with LCD screen

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard