

# 2017 RAVE



## ROTAX® ENGINE

	600 E-TEC	600 ACE
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	2
Displacement	594.4 cc	600 cc
Bore	72 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	95	95
Fuel tank	38 liters	38 liters
Oil tank capacity	3.7 liters	2.1 liters


## POWERTRAIN

Drive clutch type	TRA 3	eDrive
Driven clutch type	QRS	
Small sprocket number of teeth	25	21
Large sprocket number of teeth	45	51
Drive sprocket number of teeth	8	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

## FEATURES

Frame	REX <sup>2</sup>	Heated grips	STD
Skis	Blade	Gauge	Multifunction
Seating	1-up	Electric start	STD (ACE) Accessory (E-TEC)
Handlebar	Straight steel with hooks, 115 mm riser	Mirrors	Accessory
Reverse	RER (600 E-TEC) Mechanical (600ACE)	Windshield	S / 235 mm
		Hitch	Accessory

## COLOUR

Red/Black 

## DIMENSIONS

Vehicle overall length	3000 mm
Vehicle overall width	1245 mm
Vehicle overall height	1210 mm
Ski stance	1080 mm
Track nominal width	381 mm
Track nominal length	3269 mm
Track profile height	35 mm Cobra

## SUSPENSION

Front suspension	A-LFS+
Front shock	HPG 36
Rear suspension	PPS <sup>2</sup> -3300
Center shock	HPG 36
Rear shock	HPG 36