

2017 XTRIM SC



ROTAX® ENGINE

	600 E-TEC	900 ACE
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3
Displacement	594.4 cc	899.0 cc
Bore	72 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	8100 RPM	7250 RPM
Carburation	Electronic Direct Injection	EFI
Recommended fuel type	Premium unleaded	Regular unleaded
Minimum octane	95	95
Fuel tank	38 liters	38 liters
Oil tank capacity	3.7 liters	3.3 liters

POWERTRAIN

Drive clutch type	TRA 3	eDrive II
Driven clutch type	QRS	QRS SS
Small sprocket number of teeth	23	24
Large sprocket number of teeth	45	49
Drive sprocket number of teeth	8	

Brake system Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	REX ²	Heated grips	STD
Skis	Blade DS	Gauge	Multifunction
Seating	1-up	Electric start	STD
Handlebar	Straight steel with hooks, 160 mm riser	Mirrors	Accessory
		Windshield	L / 410 mm
Reverse	RER (600 E-TEC) Mechanical (900ACE)	Hitch	STD (J-hook)

COLOUR

White/Red 

DIMENSIONS

Vehicle overall length	3200 mm
Vehicle overall width	1170 mm
Vehicle overall height	1310 mm
Ski stance	996 +/- 21 mm
Track nominal width	406 mm
Track nominal length	3705 mm
Track profile height	39 mm DSG

SUSPENSION

Front suspension	A-LFS+
Front shock	KYB 36R
Rear suspension	PPS ² -3700
Center shock	KYB 36
Rear shock	KYB 46